

GF by AW

The GF range made with Associated Weavers: 2.0mm glue-down LVT and 5.2mm Click SPC.

COVERS All 27 GF by AW designs

Key specifications

GLUE DOWN

2.0mm, 0.55mm wear layer, plank and parquet, 16 designs

WATER

100% waterproof

GLUE DOWN CERTIFICATION

Greenguard Gold, FloorScore, French A+ VOC label

CLICK SPC

5.2mm including 1mm acoustic underlay, 0.3mm wear layer, plank and herringbone, 11 designs

UNDERFLOOR HEATING

Water and electric systems, floor max 27°C

GUARANTEE

25 years residential

The designs

Glue Down plank (8)

Design	Plank size	Thickness	Wear layer	Pack
Ardverikie Oak	178 x 1219mm	2.0mm	0.55mm	3.685m ²
Devonshire Oak	178 x 1219mm	2.0mm	0.55mm	3.685m ²
Fife Oak	178 x 1219mm	2.0mm	0.55mm	3.685m ²
Glencoe Oak	178 x 1219mm	2.0mm	0.55mm	3.685m ²
Inverlochry Oak	178 x 1219mm	2.0mm	0.55mm	3.685m ²
Lomond Oak	178 x 1219mm	2.0mm	0.55mm	3.685m ²
Nevis Oak	178 x 1219mm	2.0mm	0.55mm	3.685m ²
Skye Oak	178 x 1219mm	2.0mm	0.55mm	3.685m ²

Glue Down parquet (8)

Design	Plank size	Thickness	Wear layer	Pack
Ardverikie Oak Parquet	114 x 457mm	2.0mm	0.55mm	2.926m ²
Devonshire Oak Parquet	114 x 457mm	2.0mm	0.55mm	2.926m ²
Fife Oak Parquet	114 x 457mm	2.0mm	0.55mm	2.926m ²

Glencoe Oak Parquet	114 x 457mm	2.0mm	0.55mm	2.926m ²
Inverlochry Oak Parquet	114 x 457mm	2.0mm	0.55mm	2.926m ²
Lomond Oak Parquet	114 x 457mm	2.0mm	0.55mm	2.926m ²
Nevis Oak Parquet	114 x 457mm	2.0mm	0.55mm	2.926m ²
Skye Oak Parquet	114 x 457mm	2.0mm	0.55mm	2.926m ²

Click SPC plank (7)

Design	Plank size	Thickness	Wear layer	Pack
Atholl Oak	178 x 1219mm	5.2mm	0.3mm	2.2m ²
Balmoral Oak	178 x 1219mm	5.2mm	0.3mm	2.2m ²
Braemar Oak	178 x 1219mm	5.2mm	0.3mm	2.2m ²
Cairngorm Oak	178 x 1219mm	5.2mm	0.3mm	2.2m ²
Kintail Oak	178 x 1219mm	5.2mm	0.3mm	2.2m ²
Rannoch Oak	178 x 1219mm	5.2mm	0.3mm	2.2m ²
Torridon Oak	178 x 1219mm	5.2mm	0.3mm	2.2m ²

Click SPC herringbone (4)

Design	Plank size	Thickness	Wear layer	Pack
Aviemore Oak Herringbone	126 x 630mm	5.2mm	0.3mm	2.223m ²
Braemar Oak Herringbone	126 x 630mm	5.2mm	0.3mm	2.223m ²
Rannoch Oak Herringbone	126 x 630mm	5.2mm	0.3mm	2.223m ²
Speyside Oak Herringbone	126 x 630mm	5.2mm	0.3mm	2.223m ²

Tested performance: GF by AW Click SPC

Reaction to fire (EN 13501-1)	Bfl-s1
Slip resistance (EN 13893 / DIN 51130)	DS / R9
Use classification (EN ISO 10874)	23 domestic, 31 commercial
Residual indentation	< 0.2mm
Dimensional stability	≤ 0.10%
Castor chair	Suitable (type W castors)
Colour fastness to light	> 6

Impact sound insulation	17dB
Thermal resistance	0.076 m ² K/W
Indoor air quality	A+, formaldehyde class E1, phthalate free

Fitting, care and guarantee

Fit and look after this floor using the matching GF installation guide and care guide, and see the full guarantee terms, all at gf-flooring.uk/guides/. The Pack column shows the area one pack covers. Allow at least 10% extra for cutting.

These are the GF Flooring instructions and terms for this product, issued September 2026. For the latest version and the rest of the GF guides, visit gf-flooring.uk/guides/.