

GF Click SPC

Rigid-core click flooring with the underlay built in, in plank and herringbone.

COVERS All 45 GF Click SPC designs

Key specifications

CONSTRUCTION

Rigid stone polymer composite (SPC) core, click joints, built-in underlay

WEAR LAYER

0.5mm or 0.55mm, depending on design

DESIGNS

45, of which 20 are B&Q exclusive

UNDERFLOOR HEATING

Suitable, floor surface max 27°C

THICKNESS

4mm to 6.5mm, depending on design

FORMATS

Plank, herringbone

WATER

100% waterproof

GUARANTEE

Lifetime residential, 15 years commercial

The designs

Plank (25)

Design	Plank size	Thickness	Wear layer	Pack	
Blenheim Oak	180 x 1220mm	5mm	0.5mm	2.64m ²	
Bourton Oak	180 x 1220mm	6.5mm	0.5mm	2.2m ²	
Broadway Oak	180 x 1220mm	6.5mm	0.5mm	2.2m ²	
Burford Oak	180 x 1220mm	6.5mm	0.5mm	2.2m ²	
Campden Oak	180 x 1220mm	6.5mm	0.5mm	2.2m ²	
Cotter Oak	183 x 1220mm	4.0mm	0.55mm	2.2m ²	B&Q exclusive
Cray Ash	183 x 1220mm	4.0mm	0.55mm	2.2m ²	B&Q exclusive
Daylesford Oak	180 x 1220mm	5mm	0.5mm	2.64m ²	
Deepdale Fir	183 x 1220mm	4.0mm	0.55mm	2.2m ²	B&Q exclusive
Dent Oak	183 x 1220mm	4.0mm	0.55mm	2.2m ²	B&Q exclusive
Dormy Oak	180 x 1220mm	5mm	0.5mm	2.64m ²	
Evesham Oak	180 x 1220mm	6.5mm	0.5mm	2.2m ²	
Farncombe Oak	180 x 1220mm	6.5mm	0.5mm	2.2m ²	

Garsdale Oak	183 x 1220mm	4.0mm	0.55mm	2.2m ²	B&Q exclusive
Gayle Oak	183 x 1220mm	4.0mm	0.55mm	2.2m ²	B&Q exclusive
Hawes Oak	183 x 1220mm	4.0mm	0.55mm	2.2m ²	B&Q exclusive
Hubberholme Maple	183 x 1220mm	4.0mm	0.55mm	2.2m ²	B&Q exclusive
Kingham Oak	180 x 1220mm	5mm	0.5mm	2.64m ²	
Leoube Oak	180 x 1220mm	6.5mm	0.5mm	2.2m ²	
Lygon Oak	180 x 1220mm	5mm	0.5mm	2.64m ²	
Middleham Oak	183 x 1220mm	4.0mm	0.55mm	2.2m ²	B&Q exclusive
Norton Oak	180 x 1220mm	5mm	0.5mm	2.64m ²	
Oughtershaw Oak	183 x 1220mm	4.0mm	0.55mm	2.2m ²	B&Q exclusive
Stow Oak	180 x 1220mm	6.5mm	0.5mm	2.2m ²	
Thyme Oak	180 x 1220mm	6.5mm	0.5mm	2.2m ²	

Herringbone (20)

Design	Plank size	Thickness	Wear layer	Pack	
Blenheim Oak Herringbone	128 x 615mm	5mm	0.5mm	2.36m ²	
Burford Oak Herringbone	128 x 615mm	6.5mm	0.5mm	2.05m ²	
Campden Oak Herringbone	128 x 615mm	6.5mm	0.5mm	2.05m ²	
Cotter Oak Herringbone	118 x 590mm	5.0mm	0.55mm	2.23m ²	B&Q exclusive
Cray Ash Herringbone	118 x 590mm	5.0mm	0.55mm	2.23m ²	B&Q exclusive
Daylesford Oak Herringbone	128 x 615mm	5mm	0.5mm	2.36m ²	
Deepdale Fir Herringbone	118 x 590mm	5.0mm	0.55mm	2.23m ²	B&Q exclusive
Dent Oak Herringbone	118 x 590mm	5.0mm	0.55mm	2.23m ²	B&Q exclusive
Dormy Oak Herringbone	128 x 615mm	5mm	0.5mm	2.36m ²	
Estelle Oak	128 x 615mm	6.5mm	0.5mm	2.05m ²	
Garsdale Oak Herringbone	118 x 590mm	5.0mm	0.55mm	2.23m ²	B&Q exclusive
Gayle Oak Herringbone	118 x 590mm	5.0mm	0.55mm	2.23m ²	B&Q exclusive
Hawes Oak Herringbone	118 x 590mm	5.0mm	0.55mm	2.23m ²	B&Q exclusive
Hook Oak	128 x 615mm	6.5mm	0.5mm	2.05m ²	
Hubberholme Maple Herringbone	118 x 590mm	5.0mm	0.55mm	2.23m ²	B&Q exclusive
Kingham Oak Herringbone	128 x 615mm	5mm	0.5mm	2.36m ²	
Lygon Oak Herringbone	128 x 615mm	5mm	0.5mm	2.36m ²	
Middleham Oak Herringbone	118 x 590mm	5.0mm	0.55mm	2.23m ²	B&Q exclusive

Norton Oak Herringbone	128 x 615mm	5mm	0.5mm	2.36m²	
Oughtershaw Oak Herringbone	118 x 590mm	5.0mm	0.55mm	2.23m²	B&Q exclusive

Tested performance: designs marked B&Q exclusive

Reaction to fire (EN 13501-1)	Bfl-s1
Slip resistance, pendulum (BS 7976)	36+ (wet and dry)
Slip resistance (EN 16165 Annex B)	R10
Use classification (EN ISO 10874)	23 / 33 / 42
Abrasion group (EN ISO 660-2)	T
Residual indentation (EN ISO 24343-1)	≤ 0.20mm
Dimensional stability (EN ISO 23999)	≤ 0.15%
Curling after heat (EN ISO 23999)	≤ 0.50mm
Castor chair (EN ISO 4918)	Pass
Colour fastness to light (EN ISO 105-B02)	≥ 6
Stain resistance (EN 423)	Pass
Chemical resistance (EN ISO 26987)	Index 0
Impact sound reduction (EN ISO 10140-3)	20dB
Phthalate content (EN ISO 14389)	≤ 0.01% (pass)
VOC emissions (EN 16516)	Not detected (pass)

Test data for the other designs in this range is available on request.

Fitting, care and guarantee

Fit and look after this floor using the matching GF installation guide and care guide, and see the full guarantee terms, all at gf-flooring.uk/guides/. The Pack column shows the area one pack covers. Allow at least 10% extra for cutting.

These are the GF Flooring instructions and terms for this product, issued September 2026. For the latest version and the rest of the GF guides, visit gf-flooring.uk/guides/.