

GF Glue Down 0.3

2.0mm glue-down luxury vinyl with a 0.3mm wear layer, in plank and herringbone.

COVERS All 10 GF Glue Down 0.3 designs

Key specifications

CONSTRUCTION

Glue-down (dryback) luxury vinyl tile

WEAR LAYER

0.3mm

DESIGNS

10, all B&Q exclusive

UNDERFLOOR HEATING

Water and electric systems, floor max 27°C

THICKNESS

2.0mm

FORMATS

Plank, herringbone

WATER

100% waterproof

GUARANTEE

Lifetime residential, 10 years commercial

The designs

Plank (5)

Design	Plank size	Thickness	Wear layer	Pack	
Airton Poplar	180 x 1220mm	2.0mm	0.3mm	3.41m²	B&Q exclusive
Askrigg Birch	180 x 1220mm	2.0mm	0.3mm	3.41m²	B&Q exclusive
Grassington Oak	180 x 1220mm	2.0mm	0.3mm	3.41m²	B&Q exclusive
Litton Elm	180 x 1220mm	2.0mm	0.3mm	3.41m²	B&Q exclusive
Reeth Walnut	180 x 1220mm	2.0mm	0.3mm	3.41m²	B&Q exclusive

Herringbone (5)

Design	Plank size	Thickness	Wear layer	Pack	
Airton Poplar Herringbone	115 x 460mm	2.0mm	0.3mm	2.12m²	B&Q exclusive
Askrigg Birch Herringbone	115 x 460mm	2.0mm	0.3mm	2.12m²	B&Q exclusive
Grassington Oak Herringbone	115 x 460mm	2.0mm	0.3mm	2.12m²	B&Q exclusive
Litton Elm Herringbone	115 x 460mm	2.0mm	0.3mm	2.12m²	B&Q exclusive
Reeth Walnut Herringbone	115 x 460mm	2.0mm	0.3mm	2.12m²	B&Q exclusive

Tested performance

Reaction to fire (EN 13501-1)	Bfl-s1
Slip resistance, pendulum (BS 7976)	36+ (wet and dry)
Slip resistance (EN 16165 Annex B)	R10
Use classification (EN ISO 10874)	23 / 33 / 42
Abrasion group (EN ISO 660-2)	T
Residual indentation (EN ISO 24343-1)	≤ 0.10mm
Dimensional stability (EN ISO 23999)	≤ 0.15%
Curling after heat (EN ISO 23999)	≤ 1.0mm
Castor chair (EN ISO 4918)	Pass
Colour fastness to light (EN ISO 105-B02)	≥ 6
Stain resistance (EN 423)	Pass
Chemical resistance (EN ISO 26987)	Index 0
Impact sound reduction (EN ISO 10140-3)	3dB
Phthalate content (EN ISO 14389)	≤ 0.01% (pass)
VOC emissions (EN 16516)	Not detected (pass)

Fitting, care and guarantee

Fit and look after this floor using the matching GF installation guide and care guide, and see the full guarantee terms, all at gf-flooring.uk/guides/. The Pack column shows the area one pack covers. Allow at least 10% extra for cutting.

These are the GF Flooring instructions and terms for this product, issued September 2026. For the latest version and the rest of the GF guides, visit gf-flooring.uk/guides/.