

GF Glue Down 0.7

3.0mm glue-down luxury vinyl with a commercial-grade 0.7mm wear layer, in plank, herringbone, chevron and stone-effect tile.

COVERS All 29 GF Glue Down 0.7 designs

Key specifications

CONSTRUCTION

Glue-down (dryback) luxury vinyl tile

WEAR LAYER

0.7mm

DESIGNS

29, of which 20 are B&Q exclusive

UNDERFLOOR HEATING

Water and electric systems, floor max 27°C

THICKNESS

3.0mm

FORMATS

Plank, herringbone, chevron, stone-effect tile

WATER

100% waterproof

GUARANTEE

Lifetime residential, 20 years commercial

The designs

Plank (7)

Design	Plank size	Thickness	Wear layer	Pack	
Appletreewick Chestnut	185 x 1229mm	3.0mm	0.7mm	2.27m ²	B&Q exclusive
Bishopdale Oak	185 x 1229mm	3.0mm	0.7mm	2.27m ²	B&Q exclusive
Countersett Larch	185 x 1229mm	3.0mm	0.7mm	2.27m ²	B&Q exclusive
Embsay Walnut	185 x 1229mm	3.0mm	0.7mm	2.27m ²	B&Q exclusive
Ilkley Ash	185 x 1229mm	3.0mm	0.7mm	2.27m ²	B&Q exclusive
Rylstone Oak	185 x 1229mm	3.0mm	0.7mm	2.27m ²	B&Q exclusive
Semerwater Birch	185 x 1229mm	3.0mm	0.7mm	2.27m ²	B&Q exclusive

Herringbone (12)

Design	Plank size	Thickness	Wear layer	Pack	
Appletreewick Chestnut Herringbone	115 x 460mm	3.0mm	0.7mm	1.48m ²	B&Q exclusive
Bishopdale Oak Herringbone	115 x 460mm	3.0mm	0.7mm	1.48m ²	B&Q exclusive
Borrowdale Grey Oak Herringbone	150 x 750mm	3.0mm	0.7mm	3.62m ²	

Braithwaite Golden Oak Herringbone	150 x 750mm	3.0mm	0.7mm	3.62m ²	
Countersett Larch Herringbone	115 x 460mm	3.0mm	0.7mm	1.48m ²	B&Q exclusive
Embsay Walnut Herringbone	115 x 460mm	3.0mm	0.7mm	1.48m ²	B&Q exclusive
Eskdale Pine Herringbone	150 x 750mm	3.0mm	0.7mm	3.62m ²	
Glenridding Larch Herringbone	150 x 750mm	3.0mm	0.7mm	3.62m ²	
Ilkley Ash Herringbone	115 x 460mm	3.0mm	0.7mm	1.48m ²	B&Q exclusive
Keswick Chestnut Herringbone	150 x 750mm	3.0mm	0.7mm	3.62m ²	
Rylstone Oak Herringbone	115 x 460mm	3.0mm	0.7mm	1.48m ²	B&Q exclusive
Semerwater Birch Herringbone	115 x 460mm	3.0mm	0.7mm	1.48m ²	B&Q exclusive

Chevron (4)

Design	Plank size	Thickness	Wear layer	Pack
Cartmel Weathered Oak Chevron	158 x 710mm	3.0mm	0.7mm	3.37m ²
Elterwater Elm Chevron	158 x 710mm	3.0mm	0.7mm	3.37m ²
Patterdale Aged Oak Chevron	158 x 710mm	3.0mm	0.7mm	3.37m ²
Troutbeck Country Oak Chevron	158 x 710mm	3.0mm	0.7mm	3.37m ²

Stone-effect tile (6)

Design	Plank size	Thickness	Wear layer	Pack
Attermire Stone	300 x 600mm	3.0mm	0.7mm	3.24m ²
Brimham Stone	300 x 600mm	3.0mm	0.7mm	3.24m ²
Gordale Slate	300 x 600mm	3.0mm	0.7mm	3.24m ²
Kilnsey Marble	300 x 600mm	3.0mm	0.7mm	3.24m ²
Malham Stone	300 x 600mm	3.0mm	0.7mm	3.24m ²
Penyghent Stone	300 x 600mm	3.0mm	0.7mm	3.24m ²

Tested performance: designs marked B&Q exclusive

Reaction to fire (EN 13501-1)	Bfl-s1
Slip resistance, pendulum (BS 7976)	36+ (wet and dry)
Slip resistance (EN 16165 Annex B)	R10 plank and herringbone, R9 tile
Use classification (EN ISO 10874)	23 / 33 / 42
Abrasion group (EN ISO 660-2)	T

Residual indentation (EN ISO 24343-1)	≤ 0.10mm
Dimensional stability (EN ISO 23999)	≤ 0.15%
Curling after heat (EN ISO 23999)	≤ 1.0mm
Castor chair (EN ISO 4918)	Pass
Colour fastness to light (EN ISO 105-B02)	≥ 6
Stain resistance (EN 423)	Pass
Chemical resistance (EN ISO 26987)	Index 0
Impact sound reduction (EN ISO 10140-3)	3dB
Phthalate content (EN ISO 14389)	≤ 0.01% (pass)
VOC emissions (EN 16516)	Not detected (pass)

Test data for the other designs in this range is available on request.

Fitting, care and guarantee

Fit and look after this floor using the matching GF installation guide and care guide, and see the full guarantee terms, all at gf-flooring.uk/guides/. The Pack column shows the area one pack covers. Allow at least 10% extra for cutting.

These are the GF Flooring instructions and terms for this product, issued September 2026. For the latest version and the rest of the GF guides, visit gf-flooring.uk/guides/.