

GF Versailles

Real oak engineered wood Versailles panels, 600 x 600mm.

COVERS All 6 GF Versailles designs

Key specifications

CONSTRUCTION

Real oak top layer on a stable multi-layer base

THICKNESS

14mm

FITTING

Glue down or secret nail

WATER

Water-resistant, not waterproof

GUARANTEE

25 years

PANEL

600 x 600mm

OAK TOP LAYER

3mm

DESIGNS

6

UNDERFLOOR HEATING

Suitable, floor surface max 27°C

The designs

Versailles panels (6)

Design	Plank size	Thickness	Oak layer	Grade	Finish	Fitting	Pack
Belgrave Oak Versailles	600 x 600mm	14mm	3mm	Select	Oiled	Glue down	2.88m ²
Dorfold Oak Versailles	600 x 600mm	14mm	3mm	Select	Unfinished	Glue or nail	2.88m ²
Oulton Oak Versailles	600 x 600mm	14mm	3mm	Select	Oiled	Glue or nail	2.88m ²
Peckforton Oak Versailles	600 x 600mm	14mm	3mm	Select	Oiled	Glue or nail	2.88m ²
Rookery Oak Versailles	600 x 600mm	14mm	3mm	Select	Oiled	Glue or nail	2.88m ²
Utkinton Oak Versailles	600 x 600mm	14mm	3mm	Select	Oiled	Glue or nail	2.88m ²

Fitting, care and guarantee

Fit and look after this floor using the matching GF installation guide and care guide, and see the full guarantee terms, all at gf-flooring.uk/guides/. The Pack column shows the area one pack covers. Allow at least 10% extra for cutting.

These are the GF Flooring instructions and terms for this product, issued September 2026. For the latest version and the rest of the GF guides, visit gf-flooring.uk/guides/.